

## DURA-TRIM<sup>®</sup> 1315

- Description:* **DURA-TRIM<sup>®</sup> 1315** utilizes woven fiberglass as the reinforcement for the flexible PVC covering. The fiberglass makes the material extremely flame resistant, features very high tensile strength for its weight, and has superior dimensional stability.
- Applications:* Industrial pipe wrap; flexible ducting; quilted sound blankets; quilted aircraft insulation; headlining; decorative trim; divider curtains, etc.
- Available Colors:* Duracote's custom color laboratory can custom-match virtually any color. Please provide a Federal Color Standard 5-digit number, Duracote color number, or a color swatch.
- Compliance:* **DURA-TRIM<sup>®</sup> 1315** is manufactured to Lockheed LAC 25-858A Ty 6 Cl A.

### Typical Physical Properties

Weight	7 oz/yd <sup>2</sup>
Flame Resistance FAR 25.853	
After Flame Warp/Fill	0.0/0.0 seconds
Char Length Warp/Fill	2.9/2.8 inches
Flame Resistance LCP 86-1226	
After Flame Warp/Fill	0.0/0.0 seconds
Burn Length Warp/Fill	3.4/3.5 inches
Tensile – (Grab) FSTM 191 3136 Warp/Fill	247/211 pounds
Tear (Trapezoid) FSTM 191 3136 Warp/Fill	10.5/8.0 pounds

The information contained in this technical data bulletin is believed to be true and accurate. The data is from historical testing and should not be considered a specification. This information is to be used only as a guide. It is the responsibility of the end user to determine the suitability of our products for each specific application.

MM/c  
12/14/06