

DURAPRO® 6116

Description:	DURAPRO® 6116 is a vinyl laminated, reinforced industrial fabric with a Light Taffeta or Leatherette emboss.
Applications:	Tarpaulins, Windbreakers, Protective Curtains, Covers, Gym Mats and All-weather General Purposes
Available Colors:	4022 White, 4490 Blue, 3115 Yellow, 9800 Black, 3902 Gray, 4335 Red, 5459 Navy, 4344 Burgundy, 4539 Green
Compliance:	Registered as Flame Resistant by the California Fire Marshal (F-67101)

Test and Methods	Imperial		<u>Metric</u>	
Test and Methous	Result	Unit	Result	Unit
Weight FSTM191.5041	17 ± 1	oz/yd ²	0.58 ± 0.034	kg/m ²
Adhesion (Face/Back) ASTM D751	10 / 10 ± 1	lbs/inch	44.5 / 44.5 ± 4.4	N/25mm
Vertical Flammability (MD/CD) FSTM191.5903				
After Flame	4.9 / 4.1 ± 2	seconds	4.9 / 4.1 ± 2	seconds
Char Length	3.9 / 3.4 ± 1	inches	99.1 / 86.4 ± 25.4	mm
Hydrostatic Mullen FSTM191.5512	370	PSI	2551.1	kPa
Tear –Tongue (MD/CD) FSTM191.5134	37 / 55 ± 10	lbs	164.6 / 244.7 ± 44.5	Ν
Tensile Strength-Grab (MD/CD) FSTM191.5100	230 / 200 ± 15	lbs	1023.1 / 889.6 ± 66.7	Ν
Standard Width	62	inches	1574.8	mm
Standard Length	50	yards	45.72	m

TYPICAL PHYSICAL PROPERTIES

The information contained in this technical data bulletin is believed to be true and accurate. The typical physical properties are from historical testing and should not be considered a specification. This information is to be used only as a guide. It is the responsibility of the end user to determine the suitability of our products for each specific application.

03.01.17 JB

go beyond.

MATERIAL SOLUTIONS THAT REDEFINE PERFORMANCE

350 NORTH DIAMOND ST. • RAVENNA, OH 44266 • USA • 800.321.2252 • FAX: 330.296.5102 www.duracote.com Certified to the ISO 9001:2015 with Design