

DURAPRO® 6961

Description: DURAPRO® 6961 is a vinyl laminated, reinforced industrial fabric with a Light Taffeta emboss.

Applications: Tarpaulins, Windbreakers, Protective Curtains, Covers, Gym Mats and All-weather General Purposes

Available Colors: 4022 White, 3115 Yellow, 9800 Black, 4490 Blue, 3902 Gray, 4335 Red, 5459 Navy, 4344 Burgundy, 4539 Green

Compliance: Registered as Flame Resistant by the California Fire Marshal (F-67101) and meets the requirements of MVSS 302 Flammability

TYPICAL PHYSICAL PROPERTIES

Test and Methods	Imperial		Metric	
	Result	Unit	Result	Unit
Weight FSTM191.5041	11 ± 1	oz/yd ²	0.37 ± 0.034	kg/m ²
Adhesion (Face/Back) ASTM D751	4 / 3 ± 1	lbs/inch	17.8 / 13.3 ± 4.4	N/25mm
Vertical Flammability (MD/CD) FSTM191.5903	---	---	---	---
After Flame	1.6 / 4.0 ± 0.5	seconds	1.6 / 4.0 ± 0.5	seconds
Char Length	5.7 / 5.1 ± 0.7	inches	145 / 129.5 ± 17.8	mm
Hydrostatic Mullen FSTM191.5512	240 ± 20	PSI	1654.7 ± 137.9	kPa
Tear –Tongue (MD/CD) FSTM191.5134	38 / 31 ± 5	lbs	169.0 / 137.9 ± 22.2	N
Tensile Strength-Grab (MD/CD) FSTM191.5100	180 / 120 ± 20	lbs	800.7 / 533.8 ± 89	N
Standard Width	62	inches	1574.8	mm
Standard Length	50	yards	45.72	m

The information contained in this technical data bulletin is believed to be true and accurate. The typical physical properties are from historical testing and should not be considered a specification. This information is to be used only as a guide. It is the responsibility of the end user to determine the suitability of our products for each specific application.

03.01.17 JB