

Duracote DURUG[®] 2124

Floor Covering for Aircraft

DURUG[®] is designed for use as a floor covering of new and retrofit aircraft providing an attractive, flexible, scuff-resistant floor covering. **DURUG[®]** delivers excellent anti-fatigue properties where people are required to stand for prolonged periods of time. Available with a 1/4" (6.4 mm) closed cell, non-absorbent foam underlay.

COMPLIANCES: **DURUG[®]** is manufactured to Boeing (BMS) specification 8-28F Type III. **DURUG[®]** is flame resistant to FAR 25.853(a)(1)(ii).

RESISTANT TO: Abrasion – Static – Water – Most Oils – Chemicals – Grease – Rot – Mildew.

COLORS: Gray.

PHYSICAL PROPERTIES

	Imperial			Metric	
	BMS8-28F TY III	*Typical	Unit	*Typical	Unit
Emboss	---	20	---	20	---
Weight FSTM 191.5041	55.0 Maximum	44.0 – 49.0	oz./yd ²	1.49 – 1.66	kg/m ²
Thickness FSTM 191.5030	---	0.26	inches	6.60	mm
Vertical Flame FAR25.853(a)(1)(ii)	---	---	---	---	---
After Flame	< 15	< 15	seconds	< 15	seconds
Burn Length	< 8	< 8	inches	< 203.2	mm
Drip Time	< 5	< 5	seconds	< 5	seconds

Standard Width is 54" (1372 mm)

*NOTE: The information provided is the best currently available and has been obtained by prevailing test methods. It is true and accurate to the best of our knowledge at this time. The information is provided as guidelines, should not be considered as specifications and is subject to revision as additional knowledge and experience on this product are gained. It is the responsibility of the end user to determine the suitability of our products for their particular application.

11.03.17 DH