

## **Nexflor<sup>®</sup> Decorative NTF**

### **Floor Covering for Aircraft**

**Nexflor<sup>®</sup>** is designed to bring luxury aesthetics to the high traffic areas of the aircraft. This non-textile flooring can be used in either new or retrofit aircraft providing an attractive, flexible, scuff-resistant floor covering. Nexflor delivers excellent anti-fatigue properties where people are required to stand for prolonged periods of time. Available without an underlay or a 1/8" (3.2 mm) or 1/4" (6.4 mm) closed cell, non-absorbent foam underlay.

**COMPLIANCES:** Nexflor<sup>®</sup> is manufactured to various Lockheed (LAC) and Boeing (BMS) specifications. Nexflor is flame resistant to FAR 25.853(a)(1)(ii).

**RESISTANT TO:** Abrasion – Static – Water – Most Oils – Chemicals – Grease – Rot – Mildew

#### **TYPICAL PHYSICAL PROPERTIES\***

	<b>1/8" FOAM UNDERLAY</b>
<b>Emboss</b>	Woodgrain
<b>Certified to Specification</b>	FAR 25.853(a)
<b>Weight</b> FSTM 191.5041	27-31.2 oz/yd <sup>2</sup> (0.92 – 1.05 kg/m <sup>2</sup> )
<b>Tabor Abrasion</b> CS10, 1000g, 650	No Wear
<b>Vertical Flame</b> FAR 25.853(a)(1)(ii)	Pass
<b>Tear-Trap (MD / CD)</b> ASTM D1117	30.6 / 44.2 lbs (136.1 / 196.6 N)
<b>Surface Resistivity</b> ASTM D257	10 <sup>9</sup> – 10 <sup>12</sup> ohms (Anti-Static)
<b>Coefficient of Friction</b> BOEING BMS 8-286F	Leather & Rubber Dry: Pass Wet: Pass

**Standard Width is 54" (1372 mm) – Minimum Order is 50 linear yards (46 linear meters) per pattern.**

NOTE: The information provided is the best currently available and has been obtained by prevailing test methods. It is true and accurate to the best of our knowledge at this time. The information is provided as guidelines, should not be considered as specifications and is subject to revision as additional knowledge and experience on this product are gained. It is the responsibility of the end user to determine the suitability of our products for their particular application.

11/14/19 M.M.